

Descriptive report on the patent: invention of the
“SCREW-OFF TOP EXTRACTOR”.

This invention refers to a piece that can be
manufactured in a hexagonal format, or even in cylinder form, using disposable
05 - and low cost materials. It is meant to be used on the neck of beverage bottles with
screw-on tops.

The tops used to seal beverage bottles present
external slits made by the equipment used to seal these bottles. For this reason,
the screw-on type bottles, created to facilitate their opening, end up presenting
10 - some inconveniences, such as: the top must be submitted to great pressure at the
time of capping, and therefore will require lots of physical force in order to unscrew;
also, due to the external slits in such tops, many times the person may injure his or
her hands attempting to open them; furthermore, when the person is unable to
unscrew the top with their bare hands they may end up using the edge of their shirt
15 - or T-shirt while attempting to unscrew the top and end up damaging their clothing,
therefore generating financial loss.

Trying to find a solution to these problems the
present invention of the **“SCREW-OFF TOP EXTRACTOR”** was developed. It can
be manufactured with disposable and low cost materials, which can be presented
20 - externally in a hexagonal format to facilitate the torsion movement of unscrewing
the top from the bottle, or even in other outer formats, like a cylindrical form for
example.

The drawings attached show with precision the
manufacturability and functional disposition applied in this **“SCREW-OFF TOP
25 - EXTRACTOR”**, where:

Figure 1 shows a top view of the extractor;

Figure 2 shows a view of the bottom of the
extractor;

Figure 3 shows a lateral view in perspective of
30 - the extractor;

Figure 4 shows the extractor from a lateral-
top view;

Figure 5 shows the extractor from a lateral bottom;

Figure 6 shows, in an enlarged view, an illustration of a bottle with the screw threads on the neck, an extractor, and the top;

05 - **Figure 7** shows an illustration of a bottle with the extractor on the bottleneck and the screw on top above the bottle;

Figure 8 shows the same illustration seen in figure 7 but, now with the top already screwed on, and the extractor below the top and fixed to the bottleneck.;

10 - **Figure 9** shows an illustration of the extractor when it is raised into the position where its' internal slits fit into the external slits of the bottle top;

Figure 10 shows an illustration of the rotation used to unscrew the bottle top pushing the extractor upward in order to facilitate
15 - the opening of the bottle; both the top and extractor can then be discarded.

As shown in the attached drawings, we have:
The extractor (01) that has on its upper part the slits (02) and on the bottom part a conical form (03).

In this way, the extractor can be manufactured
20 - with a conical internal opening (03) so that the upper side contains the slits (02) on the bottom, and the opening of the inferior part of the extractor (01) is larger than the upper opening that contains the slits (02) that will fit into the external slits on the bottle top (04).

The extractor (01) in conical form (03) from top
25 - to bottom will permit that once incased on the neck of the bottle (06) it will stay in place (05) ready to be pulled up and have its internal slits (02) incase into the external slits of the bottle top (04) and allow an easy opening of the pressure placed on the bottle top without traumas.